

PACKAGE RECEIVER TLR 30X6 / TL 30X6



DRIVE UP SOLUTIONS

TLR 30X6 TL 30X6 HIGH SECURITY SAFE



*CS-12000 Monolith
in Door & Body*

*Convenient Pull
Handle*

*Stainless Facial
Panel*

*Massive 3 Way
Active Boltwork
Including
Two Bolts Up and
Two Bolts Down*

*Adjustable Ball
Bearing Hinges*

*Megasteel
Antipenetration
Plate Covering
Door*

*Push and Pull
Boltwork
Mechanism*

*Glass Plate with 6
Relocking Devices
(Inside)*

TLR 30X6 TL 30X6 HIGH SECURITY SAFE



PACKAGE RECEIVER TLR 30X6 / TL 30X6

SIX-SIDED PROTECTION + FIRE PROTECTION

SENTRY is proud to introduce to you its new TL-30 high security safe. Designed, tested, and built by one of the most experienced teams of high security safes experts ever assembled. The same team that succeeded with the only U.L. approved TXTL-60 safe in the world. The SENTRY TL-30 is unsurpassed in its ability to withstand the most concentrated burglary attacks. SENTRY manufactures an additional variety of U.L. tested high security safes and vaults. With SENTRY you enjoy a track record of manufacturing, supplying, and servicing high security safes...

DOOR

The Money Teller TL-30 door is constructed of inner and outer electrically welded steel plates enclosing SENTRY's new superior barrier composite material CS-12000. In addition to the CS-12000 monolith, the entire door is covered by drill resistive "megasteel" antipenetration plates and our "Z" reinforcement bars. The entire door has overall thickness of 7.1" (180mm). The combination of SENTRY's barrier materials provide the door a unique strength to protect against tool and torch attacks.

BODY

The Money Teller TL-30 body is constructed of inner and outer

electrically welded steel plates including our "Z" reinforcement bars welded to the inner and outer body that together with SENTRY's CS-12000 monolith and the reinforcement special alloy grid performs a 3.5" (90mm) unique strong body.



being opened. In addition, both locks are connected to two live relockers. A floating connection between the locks and the live relockers ensures that every time the safe is locked, the relockers will move into the locked position. For additional lock protection and control, every door is prepared to accept a time lock.

FIRE RESISTANCY

The Megasafe Jewelers TL-30 safe has been fireproofed and heat tested for two hours according to the most difficult standards.

INTERIOR EQUIPMENT

Adjustable/removable shelves are standard, plus a variety of drawers, lockers, and interior compartments are available as optional extras.



BOLTWORK AND RELOCKING MECHANISM

SENTRY's patented "solo" 3 way push and pull locking mechanism activates massive 1 1/2" (38mm) bolts. A continuous, reinforced interlock rail secures the door on the hinge side. The vital mechanism areas are protected by a glass plate. An attack by tool, torch or explosives will shatter the glass activating four relocking devices thus preventing the safe from

